

**DEMO**

**Instant  
Download  
After  
Purchase**

**100%  
Money  
Back  
Guarantee**

**PDF**  
FILE FORMAT

**90  
Days  
Free  
Updates**

# **CISCO 600-512**

## **Q&As**

2020 Latest EXAMSDUMPS 600-512 PDF Dumps Download. Following Questions and Answers are all new published by Cisco Official Exam Center

- **Latest 600-512 Dumps**
- **600-512 Practice Test**
- **600-512 Study Guide**

**Pass CISCO 600-512 Exam  
with 100% Guarantee**

Free Download Real  
Questions & Answers  
PDF and VCE file from:



+13069525559



<https://examsdumps.co/>



<https://www.facebook.com/examsdumps.co/>

Number: 600-512  
Passing Score: 800  
Time Limit: 120 min

CISCO

**600-512**

**Implementing with Cisco Network Programmability for ACI**

**Sections**

1. Requirements Collection and Analysis
2. Deployment Design Development
3. Configuration and Implementation
4. Troubleshooting
5. Operation and Optimization

## Exam A

### QUESTION 1

Which two options are supported in the ACI API to query the MIT tree? (Choose two.)

- A. by distinguished name
- B. by class
- C. by role
- D. specific objects by UUID
- E. objects by master replica

**Correct Answer:** AB

**Section:** Requirements Collection and Analysis

**Explanation**

**Explanation/Reference:**

### QUESTION 2

When a subnet is configured as "private subnet" within a bridge domain, what is the desired behavior for the subnet?

- A. Private VLANs are enabled.
- B. The subnet is not routed within the private network.
- C. The subnet is not routed outside the ACI fabric.
- D. The subnet is routed between tenants.

**Correct Answer:** C

**Section:** Deployment Design Development

**Explanation**

**Explanation/Reference:**

### QUESTION 3

An ACI fabric is being connected to an existing switch network. Which spanning tree protocol must be configured to enable flooding in the native VLAN to ensure a loop-free topology?

- A. PVST
- B. MST

- C. Rapid PVST
- D. legacy STP

**Correct Answer:** B

**Section:** Deployment Design Development

**Explanation**

**Explanation/Reference:**

#### **QUESTION 4**

Which option is the default mode for policy propagation to leaf switches?

- A. policy preconfiguration
- B. policy prepopulation with on-demand configuration
- C. no policy prepopulation
- D. policy prepopulation

**Correct Answer:** B

**Section:** Deployment Design Development

**Explanation**

**Explanation/Reference:**

#### **QUESTION 5**

When you create a vCenter domain, which two options are available to choose a virtual switch? (Choose two.)

- A. VMware Standard vSwitch
- B. Cisco AVS
- C. Open vSwitch
- D. VMware Distributed Switch
- E. Cisco ASA v

**Correct Answer:** BD

**Section:** Deployment Design Development

**Explanation**

**Explanation/Reference:**

### QUESTION 6

Which option is a valid connection for the fabric port on a leaf switch?

- A. connected to spine
- B. connected to fabric port on a different leaf
- C. connected to a downstream FabricPath domain
- D. connected to an Cisco APIC controller
- E. connection to an ESX host

**Correct Answer:** A

**Section:** Deployment Design Development

**Explanation**

**Explanation/Reference:**

### QUESTION 7

Which three types of subnet scope can be created in ACI? (Choose three.)

- A. Public, which is advertised to the external router by the border leaf
- B. Private, which is visible only to the local context
- C. Shared, which is visible only to the shared context
- D. Querier, which enables IGMP snooping on the subnet
- E. RFC 3021 subnets, which use /31 host addresses on both ends of a point-to-point link

**Correct Answer:** ABC

**Section:** Deployment Design Development

**Explanation**

**Explanation/Reference:**

### QUESTION 8

Which option lists the correct steps in the correct order that are needed to enable MP-BGP in within ACI fabric?

- A. Create A route reflector policy, create a POD policy group, and apply the POD policy group to the POD.
- B. No configuration is required because this is provisioned automatically by the Cisco APIC.
- C. Create a route reflector policy, create an EPG in the infra tenant containing all of the switches, and apply the route reflector policy to the EPG.
- D. Create a route reflector policy, and attach the route reflector policy to each tenant that an address family should be created for.

**Correct Answer:** A

**Section:** Configuration and Implementation

**Explanation**

**Explanation/Reference:**

